




STOCK CLEARANCE JULY 2017


Aquarius Cable						
	Description	Technical Data	Length	Retail	Special	Stock
	Moulded Power Cable used as entry level alternative to Extreme cable for Aquarius Fitted with Schuko and IEC C19 plugs	Conductor: 3 x 1,5 mm ² Power Rating: 10 A Insulation: High Quality PVC Shielding: None Resistance: < 8 Ω / km	2,0 metre	195	135	1
Premier Mains Cable GII & EVO3						
	Description	Technical Data	Length	Retail	Special	Stock
	Double Shielded OFC Conductors High quality IEC C7 (figure 8) plug MK SABS Duraplug (GII) or BS-1363 Fused UK plug (EVO3)	Conductor: 3 x 1,5 mm ² Power Rating: 2,5 A Insulation: High Quality PVC Shielding: Aluminium/Polyester Resistance: < 8 Ω / km	1,5 metre	1 385 1 385	970 970	3 GII 5 EVO3
Premium Mains Cable GII						
	Description	Technical Data	Length	Retail	Special	Stock
	Double Shielded OFC Conductors High quality IEC C15 plug MK SABS Duraplug	Conductor: 3 x 1,5 mm ² Power Rating: 10 A Insulation: High Quality PVC Shielding: Aluminium/Polyester Resistance: < 8 Ω / km	1,5 metre	1 625	1 135	9
Elite Mains Cable GII						
	Description	Technical Data	Length	Retail	Special	Stock
	Double Shielded OFC Conductors High quality IsoTek 24 ct gold IEC C15 plug MK SABS Duraplug	Conductor: 3 x 1,5 mm ² Power Rating: 10 A Insulation: High Quality PVC Shielding: Aluminium/Polyester Resistance: < 8 Ω / km	1,5 metre	2 855	2 000	8
Optimum High Current Mains Cable GII						
	Description	Technical Data	Length	Retail	Special	Stock
	Triple Shielded OFC Conductors High quality IsoTek 24 ct gold IEC C15 plug MK SABS Duraplug	Conductor: 3 x 2,5 mm ² Power Rating: 20A Insulation: High Quality PVC Shielding: Aluminium/Polyester Resistance: < 8 Ω / km	1,5 metre	5 715	4 000	6
IsoTek 24 ct Gold Connectors						
	24 ct Gold Schuko + IEC C15 pack	Complete with heatshrink and cable end crimping sleeves	Cable external diameter of 4-16mm	2 210	1 545	0
	24 ct Gold US 3-pin + IEC C15 pack	Complete with heatshrink and cable end crimping sleeves		2 210	1 545	1
	24 ct Gold, Single pack: IEC C15			750	525	31
	24 ct Gold, Single pack: IEC C7			750	525	4
	24 ct Gold, Single pack: US 3-Pin			750	525	0
	24 ct Gold, Single pack: EU Schuko			750	525	0
Protek Filter DISCOVERY RANGE						
	Description			Retail	Special	Stock
	Plug-in two pin (Euro) intelligent protection system ensuring spike and surge suppression at noise sources and/or AV system appliances			1 385	970	5
Mira Filter EVO3						
	Description	Technical Data	Outputs	Retail	Special	Stock
	For Audio-Visual Applications Huge 700 Joule surge protection Extends connected components' life Improves sound & picture quality Eradicates cross component contamination	Mains Outlets: x 2, SABS Aerial : x1, F-Type Socket Power Input: Fused IEC Mains Voltage: 230VAC/50-60Hz Maximum Current: 10 A Dimensions:(WxHxD) 95x85x155 mm	2 SABS 1 Aerial	4 240	2 965	1


PERFORMANCE RANGE

Gemini GII						
	Description	Technical Data	Outputs	Retail		
	Ideal for complete systems (2, 4, 6 or 8 sockets) Eradicates cross component contamination Individually filtered sockets Polaris-X network + Delta + Protection filters	Socket type: SABS Power Input: Fused IEC Mains Voltage: 230VAC/50-60Hz Maximum Current 1&2: 10 A Dimensions: (WxHxD) 120x80x410/555/700 mm	2-Way Unit	4 525	3 165	1
			8-Way Unit	6 500	4 550	1

Wall Bracket						
	Description	Technical Data				
	Wall mounting bracket which allows Gemini and Orion to be positioned either vertically or horizontally.	Set includes 2x U-shape brackets, 1x L-shape bracket (for vertical fixing), screws and rawl-plugs		316	220	7

Titan High-End Power Conditioner GII						
<i>SELECT RANGE</i>						
	Description	Technical Data	Colour			
	Designed for all Audio & Visual components Virtually Unrestricted Power handling Sophisticated Electronic Fusing Compact, Elegant Design Expandable, via Multi-Link output Resonance damping RDC 3 Feet Polaris-X network + Shunt + Series filters	Number of Mains Outlets: Multi-Link 6 Power Input: Neutrik Mains Voltage: 230 VAC/50-60 Hz Maximum Current: 16 A Overall Performance : 3 680 Watt Stress Peaks: Unlimited	Multi-Link Silver	10 425	7 295	1

IsoTek Full System Enhancer CD						
	Description	Technical Data		Retail	Special	Stock
	65 Minutes "Burn-In"- and demagnetisation tracks Reduces 'Burn-In' time for new components Improves Sound Quality	Number of Tracks: 3 Play Time: 65 Minutes	Per piece	300	210	4

IsoTek Ultimate System Set-Up CD						
	Description	Technical Data				
	20 tracks to help set up, test and fine-tune your audio system: 14 Set up tracks 6 music tracks from OPUS 3	Number of Tracks: 20	Per piece	325	225	11

Blue Horizon Profono Phono Pre-Amplifier						
		Technical Data				
	<ul style="list-style-type: none"> 1 cartridge impedance matching sockets 2 aluminium case for superior shielding 3 multi power layer socket 4 RCA phono output sockets 5 cartridge selector for MM, MC low and high 6 RCA phono input sockets 	Gain: MM: 41 dB MC (low): 50 dB MC (high): 61 dB Input Resistance: 47 KΩ, 1 KΩ, 470 Ω, 100 Ω + custom values External power supply		10 175	7 120	1

All prices are in ZAR, inclusive of 14% VAT and are ex Lowveld Audio, White River.

Lowveld Audio
P.O. Box 1142
White River
1240

Tel: 013 758 1836
Fax: 086 621 2366
info@lowveldaudio.co.za
www.lowveldaudio.co.za

Banking Details: Lowveld Audio
ABSA Bank
Nelspruit Branch
Branch Code: 334-252
Account No. : 406 726 1348